



# **SYSLOG AND WEBADM**

The specifications and information in this document are subject to change without notice. Companies, names, and data used in examples herein are fictitious unless otherwise noted. This document may not be copied or distributed by any means, in whole or in part, for any reason, without the express written permission of RCDevs Security.

WebADM and OpenOTP are trademarks of RCDevs. All further trademarks are the property of their respective owners.

No guarantee is given for the correctness of the information contained in this document. Please send any comments or corrections to [info@rcdevs.com](mailto:info@rcdevs.com).

# Syslog and WebADM

[SIEM](#) [Splunk](#) [syslog](#) [rsyslog](#) [WebADM](#)

## 1. Overview

This HowTo describes how to configure WebADM to send logs to the local syslog and optionally after to a remote syslog (rsyslog) server. Procedure may change according to the operating system, this configuration has been tested with CentOS Stream and RHEL OS. Please, refer to Rsyslog documentation for more information.

## 2. Configuration

### 2.1 WebADM configuration

On WebADM side, you need to edit the following configuration file :

```
/opt/webadm/conf/webadm.conf
```

Then you have to configure/enable the following settings:

```
log_syslog yes
syslog_facility LOG_LOCAL0
syslog_format CEF
```

Here, we are using the syslog facility local0 and the logs format is configured to the CEF which is a standard for every SIEM solutions.

Restart WebADM with the following command in order for changes takes effect:

```
/opt/webadm/bin/webadm restart
```

WebADM configuration is done.

### 2.2 Syslog configuration

WebADM is now configured to send logs to `/var/log/local0.log`. If the file does not already exist, you have to create it.

```
touch /var/log/local0.log
```

Set the proper permissions to `/var/log/local0.log` file:

```
chmod 600 /var/log/local0.log
chown root:root /var/log/local0.log
```

Now, configure the following in `/etc/rsyslog.conf`:

```
#### RULES ####

local0.*                /var/log/local0.log
```

Restart syslog and rsyslog services.

```
systemctl restart rsyslog
systemctl restart syslog
```

## 2.3 Verification

WebADM logs should now be sent to `/var/log/local0.log`

```
cat /var/log/local0.log
...
Aug  9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|New
openotpNormalLogin SOAP request|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20
spt=50652 dst=192.168.4.20 dpt=8080 request=/openotp/index.php?
token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug  9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|> Username:
yoann|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 dst=192.168.4.20
dpt=8080 request=/openotp/index.php?
token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug  9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|> Domain:
SUPPORT|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 dst=192.168.4.20
dpt=8080 request=/openotp/index.php?
token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug  9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|> LDAP
Password: xxxxxxxx|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652
dst=192.168.4.20 dpt=8080 request=/openotp/index.php?
token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug  9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|> Client ID:
LDAP|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 dst=192.168.4.20
dpt=8080 request=/openotp/index.php?
token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164
```

token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|> Source IP: 192.168.3.132|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|> Context ID: f3b109f26a25b60a839984340c68ac56|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|> Options: WEBAUTH|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Enforcing client policy: LDAP (matched client ID)|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Registered openotpNormalLogin request|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Ignoring 3 groups for user 'CN=yoann ,OU=SUPAdmins,DC=support,DC=rcdevs,DC=com' (out of domain group search base)|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Resolved LDAP user: CN=yoann ,OU=SUPAdmins,DC=support,DC=rcdevs,DC=com|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|New openotpNormalLogin request (SUPPORT\yoann)|1|event=sql rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Started transaction lock for user|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Found user language: FR|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Found 1 user mobiles: +33xxxxxxx|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Found 1 user emails: yoann@suppot.rcdevs.com|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Found 48 user settings: LoginMode=LDAP,OTPTType=TOKEN,OTPFallback=SMS,PushLogin=No,PushVoice=No,LockTimer=5,MaxTries: 1:HOTP-SHA1-6:QN06-T1M,DeviceType=FIDO2,U2FPINMode=Discouraged,SMSType=Normal,SMSMode=Ondemand,ReplyData=[1 Items],MailMode=Ondemand,PrefetchExpire=10,LastOTPTime=300,ListChallengeMode=ShowID|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Found 8 user data: OTPPrefix,AppKeyInit,VoiceState,TokenType,TokenKey,TokenState,TokenID,TokenSerial|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Requested login factors: LDAP|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|LDAP password Ok|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Updated user data|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php? token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d5355504164

Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Authentication success (LDAP)|1|event=sql rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652 suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php?

```
suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php?  
token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d53555041646
```

```
Aug 9 12:09:40 webadm1 webadm[2170148]: CEF:0|RCDevs|WebADM|2.1.13|OpenOTP|Sent login  
success response|1|event=file rt=1660039780 sid=8QCFTXC6 src=192.168.4.20 spt=50652  
suser=192.168.3.132 dst=192.168.4.20 dpt=8080 request=/openotp/index.php?  
token=5a5033bdbf34310a91267ae582e6fa680000434e3d796f616e6e2074726175742c4f553d53555041646
```

The structure of the generated logs in CEF format is the following:

DATE | SERVER NAME | Process Name & PID | LOG FORMAT | Product Provider | Product name | Product version | Web Service/Application name | Request summary | severity | Log details

### 3. Configure syslog to send logs to a remote syslog server

In order to send local syslog logs to a remote syslog, you have to edit the file `/etc/rsyslog.conf` and add the following:

```
local0.* action(type="omfwd"  
queue.type="linkedlist"  
queue.filename="rcdevs_fwd"  
action.resumeRetryCount="-1"  
queue.saveOnShutdown="on"  
target="192.168.10.250" port="514" protocol="tcp"  
)
```

Just replace the target and port by your Rsyslog IP address/hostname, port and protocol if needed according to your Rsyslog server configuration. On my side it is 192.168.10.250, port 514/TCP.

Restart syslog and rsyslog services.

```
systemctl restart rsyslog  
systemctl restart syslog
```

Logs should now be sent to your Rsyslog server.

*This manual was prepared with great care. However, RCDevs Security S.A. and the author cannot assume any legal or other liability for possible errors and their consequences. No responsibility is taken for the details contained in this manual. Subject to alternation without notice. RCDevs Security S.A. does not enter into any responsibility in this respect. The hardware and software described in this manual is provided on the basis of a license agreement. This manual is protected by copyright law. RCDevs Security S.A. reserves all rights, especially for translation into foreign languages. No part of this manual may be reproduced in any way (photocopies, microfilm or other methods) or transformed into machine-readable language without the prior written permission of RCDevs Security S.A. The latter especially applies for data processing systems. RCDevs Security S.A. also reserves all communication rights (lectures, radio and television). The hardware and software names mentioned in this manual are most often the registered trademarks of the respective manufacturers and as such are subject to the statutory regulations. Product and brand names are the property of RCDevs Security. © 2024 RCDevs Security S.A., All Rights Reserved*